

ABout Time Linux - the requirements

Eric D. Schabell
erics@abtlinux.org

May 24, 2006

Abstract

This document will detail a project that has risen from the desire to create a generic framework for managing the software on a Linux system. It is based on my experiences while working as a developer on a source-based Linux distribution spanning more than three years at the time of this writing.

I hope to take my experiences as a developer and package maintainer to create this new package manager. I follow in the footsteps of a few pretty good existing projects such as (micropkg, 2004), (Easinstaller, 2004) and (SMGL, 2004), though I have found these to be lacking in some way or another.

1 Introduction

The *About Time Linux (AbTLinux)* package managers design will be dealt with in this document. I will cover them in the following sections:

1. **Use Cases** - clearly defined requirements.
2. **Scenarios** - use cases worked out in clear examples.
3. **Design** - details of *AbTLinux* design, worked out in *UML* diagrams.

The driving force behind this project is to design a basic software package management system that will provide the needed infrastructure to not only install software packages, but also be able to maintain the systems it is installing the software packages onto. I believe this can be done using source based packages and by avoiding the existing RPM and DEB package management systems. This is not new, nor do I pretend to have found the Holy Grail of package management tools. The primary goal is a well documented design, with clearly documented coding practices which will result in an easily maintainable package manager. This in turn will be the foundation of this Linux distribution. Make no mistake about it, the clarity of design and coding practices will take the foremost priority in this project.

I will present my ideas in the following sections starting with the use cases that will be used to detail the requirements. These will be followed by scenarios which provide explicit examples for each requirement. Furthermore, I will put forth a design for a package management system, which will include implementation choices such as the language and system requirements.

2 Use Cases

The requirements for this project are to be defined through *Use Cases* and are the basis for an initial 1.0 release. I wish for the final set of requirements to be those needed to define a basic framework to manage the software on a Linux machine. I consider these to provide that basic functionality:

2.1 General

This section details items that are global in nature the *AbTLinux*:

- source-based distro, binary as a bonus.
- provide configuration file tools (view, edit, diff for smooth package updates).
- suggest to install package if not installed and a command is entered from that package.
- the abt package manager will be a command line interface.

2.2 Packages

This section details the requirements related to the packages themselves:

- install package
 - if new install, just do it and generate logs.
 - if upgrade, install over, compare old/new logs to delete what is not new.
- reinstall a package, either from cached build or rebuild/reconfigure.
- remove package (includes check for lone package dependencies, ask user if wants to remove them)
- downgrade a package to previous version
- freeze a package in its current state (version holding)

2.2.1 Install package

| | |
|--------------------------------|--|
| Use Case Name: | Install package |
| Description: | The basic steps to be taken to install a software package. |
| Actors: | User |
| Preconditions: | Package description is available. |
| Triggers: | abt install <pkg> |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User submits an install package request. 2. Package to be installed is placed in install queue. 3. Dependencies for this package are checked. 4. <i>Details</i> section of package is processed. 5. <i>Pre</i> section of package is processed. 6. <i>Configure</i> section of package is processed. 7. Copy of configuration is saved. 8. <i>Build</i> section of package is processed. 9. Copy of build is saved. 10. <i>Preinstall</i> section of package is processed. 11. <i>Install</i> section of package is processed. 12. A list of installed files is saved. 13. An integrity check is created on each installed file and saved. 14. <i>Post</i> section of package is processed. 15. Package is added to installed packages list. 16. Package is removed from install queue. 17. Package build is cached for future usage. 18. Package sources (build directories) are cleaned up (removed). 19. User is notified that package was successfully installed. |

| | |
|-------------------------------|--|
| <p>Exceptions:</p> | <ol style="list-style-type: none"> 1. The package is already installed, report this and terminate with success. 2. The <i>details/pre/prebuild/preinstall/post</i> sections fail, report error and process stops. 3. <i>Configure</i> section fails, report error, save copy of configuration and process stops. 4. <i>Build</i> section fails, report error, save copy of build log and process stops. 5. <i>Install</i> section fails, report error, clean up any installed files (all or nothing is installed) and process stops. 6. Dependency breakage detected, add broken package to install queue. 7. Existing configuration files detected during installation of new files, query user to either; backup old versions and replace with new, keep old in place and copy new one next to it, replace old with new, default to the first choice. |
| <p>Postconditions:</p> | <ol style="list-style-type: none"> 1. Package is installed. 2. For existing packages, when error is reported, then package is still in install queue. 3. For broken dependencies, package added to install queue. |

2.2.2 Reinstall package

| | |
|--------------------------------|---|
| Use Case Name: | Reinstall package |
| Description: | The basic steps to be taken to reinstall (from cache or rebuild) a software package. |
| Actors: | User |
| Preconditions: | Package description is available and installed on system. |
| Triggers: | abt reinstall <pkg> |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User submits a reinstall package request. 2. User asked, install cached version or rebuild package. 3. Rebuild requested, add to install queue. 4. Dependencies for this package are checked. 5. Previous configuration details available, query for reconfigure. 6. <i>Details</i> section of package is processed. 7. <i>Pre</i> section processed, reconfigure only if requested. 8. <i>Configure</i> section of package processed. 9. Copy configuration is saved. 10. <i>Build</i> section of package is processed. 11. Copy of build is saved. 12. <i>Preinstall</i> section of package processed. 13. <i>Install</i> section of package is processed. 14. List of installed files is saved. 15. An integrity check is created on each installed file and saved. 16. <i>Post</i> section of package is processed. 17. Package is added to installed packages list. 18. Package removed from install queue. 19. Package sources (build directories) are cleaned up (removed). 20. Dependencies on this package are checked. 21. User is notified that package was successfully reinstalled. |

| | |
|-------------------------------|--|
| <p>Exceptions:</p> | <ol style="list-style-type: none"> 1. Any failures will result in created files (configuration and/or build) being saved with timestamp in file name. 2. Any previous timestamped (unsuccessful reinstalls) will be removed, but original successful installs will remain. 3. Any failures will result in user being given an error message with failure location information. 4. Dependency breakage detected, add broken package to install queue. 5. Existing configuration files detected during installation of new files, query user to either; backup old versions and replace with new, keep old in place and copy new one next to it, replace old with new, default to the first choice. |
| <p>Postconditions:</p> | <ol style="list-style-type: none"> 1. Package is reinstalled from cached version or rebuilt. 2. New reinstall configuration, build, install and integrity files replace original installed files. 3. For rebuild reinstalls (not for cached reinstalls) that fail, the package remains in the install queue. 4. For broken dependencies, package added to install queue. |

2.2.3 Remove package

| | |
|--------------------------------|---|
| Use Case Name: | Remove package |
| Description: | Remove an installed package. |
| Actors: | User |
| Preconditions: | Requested package is installed. |
| Triggers: | abt remove <pkg> |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User submits a remove package request. 2. Check for dependency breakage, report for user input. 3. Package is added to uninstall queue. 4. Tarball is created containing the following: <ol style="list-style-type: none"> (a) Copy of installed configuration files. (b) Copy of configuration. (c) Copy of build. (d) List of installed files. (e) List of integrity checks for installed files. (f) Copy of installed files. (g) Copy of source files for this version. (h) Copy of package data (detail, pre, configure, etc). 5. Installed package files are removed. 6. Package is removed from installed packages list. 7. Package is removed from uninstall queue. 8. Check for dependency breakage. 9. User is notified that package was successfully uninstalled. |
| Exceptions: | If package not installed, exit with success. |
| Postconditions: | <ol style="list-style-type: none"> 1. The package is no longer installed. 2. There is a tarball containing everything needed to re-create the package that was just removed. 3. For broken dependencies, package added to install or uninstall queues. |

2.2.4 Downgrade package

| | |
|--------------------------------|---|
| Use Case Name: | Downgrade a package |
| Description: | Downgrade an installed package to a previously built version. |
| Actors: | User |
| Preconditions: | Previously requested version must be available. |
| Triggers: | abt downgrade <pkg> [version] |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User submits a request to downgrade a package. 2. Check for dependency breakage, report for user input. 3. If User requests specific version and it is available we run <i>reinstall use case</i> for the cached version. 4. if no version selected or version not available, User presented with a list of previously cached versions. 5. User selects version to install. 6. Using package versions tarball (contains all data saved on <i>remove package use case</i>), User is led through the <i>reinstall package use case</i>. 7. Check for dependency breakage. 8. User is notified that package was successfully downgraded to selected version. |
| Exceptions: | Requested versions are not available (empty list of cached versions), exit with error message. |
| Postconditions: | <ol style="list-style-type: none"> 1. Requested package version has been installed, downgrading installed package version. 2. For broken dependencies, package added to install or uninstall queues. |

2.2.5 Freeze package

| | |
|--------------------------------|---|
| Use Case Name: | Freeze a package |
| Description: | Freeze a package at the currently installed version to prevent updates. |
| Actors: | User |
| Preconditions: | Package must be installed. |
| Triggers: | abt freeze <package> |
| Basic Course of Events: | <ol style="list-style-type: none">1. User requests a package be frozen at current version number.2. User given chance to add a text note to frozen status.3. Package install list is annotated to show frozen status.4. User is notified that package has been frozen. |
| Exceptions: | <ol style="list-style-type: none">1. If package not installed then offer to install and freeze package.2. If package already has status frozen, complete process as if reset to frozen. |
| Postconditions: | <ol style="list-style-type: none">1. Package has been marked with status frozen.2. Package will not be queried for possible upgrade (version increase) |

2.3 Queries

This section details items related to queries a user / administrator would need to be able to make on *AbTLinux* machines:

- show package details
- show installed packages
- show package install
- show package build
- show frozen packages
- show package dependencies
- show untracked files on system
- show journal
- show package that a file comes from
- search package description
- show install queue (all builds will be via a queue)
- show available update patch list (before retrieving them)

2.3.1 Show package details

| | |
|--------------------------------|--|
| Use Case Name: | Show package details |
| Description: | Display the given packages details. |
| Actors: | User |
| Preconditions: | Package tree is available. |
| Triggers: | abt show-details <pkg> |
| Basic Course of Events: | <ol style="list-style-type: none">1. User requests a show package.2. Package details displayed:<ol style="list-style-type: none">(a) name(b) version(c) author(d) source location(e) last package update(f) dependencies(g) description(h) installed version(i) available version (from abt repository) |
| Exceptions: | none. |
| Postconditions: | User has seen the given packages details. |

2.3.2 Show installed packages

| | |
|--------------------------------|---|
| Use Case Name: | Show installed packages |
| Description: | Display a formatted listing of the installed packages. |
| Actors: | User |
| Preconditions: | Package install listing and network is available. |
| Triggers: | abt show-installed |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User requests an installed packages report. 2. Access the installed packages listing. 3. Access the remote update listing for most recent package versions. 4. List presented containing the installed package details: <ol style="list-style-type: none"> (a) name (b) date (c) installed version (d) available version local (e) available version abt repository |
| Exceptions: | Remote package update listing is not available, complete report by filling in nothing for available version. |
| Postconditions: | User has been presented an overview of the installed packages. |

2.3.3 Show package install

| | |
|--------------------------------|---|
| Use Case Name: | Show package install |
| Description: | Display a listing of the files installed for given package. |
| Actors: | User |
| Preconditions: | Package requested is installed. |
| Triggers: | abt show-files <pkg> |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User requests to view a listing of the files installed by a package. 2. A dump is given of the installed files log for the package. |
| Exceptions: | Missing file log, report error. |
| Postconditions: | User has been presented a listing of the files installed by a package. |

2.3.4 Show package build

| | |
|--------------------------------|--|
| Use Case Name: | Show package build |
| Description: | Display the build log for given package. |
| Actors: | User |
| Preconditions: | Package requested has been built previously. |
| Triggers: | abt show-build <pkg> |
| Basic Course of Events: | <ol style="list-style-type: none">1. User requests to view the most recent build log for package.2. A dump is given of the most recent build log for the package. |
| Exceptions: | Missing build log, report error. |
| Postconditions: | User has been presented a log of the given packages build. |

2.3.5 Show frozen packages

| | |
|--------------------------------|---|
| Use Case Name: | Show frozen packages |
| Description: | Display all packages with a frozen status. |
| Actors: | User |
| Preconditions: | none. |
| Triggers: | abt show-frozen |
| Basic Course of Events: | <ol style="list-style-type: none">1. User requests a list of frozen packages.2. The installed package list is used to determine which packages need to be checked.3. Packages that are determined to be frozen are displayed. |
| Exceptions: | Missing install log, report error. |
| Postconditions: | User has been presented a list of frozen packages. |

2.3.6 Show packages dependencies

| | |
|--------------------------------|--|
| Use Case Name: | Show package dependencies |
| Description: | Display the dependency tree for a given package. |
| Actors: | User |
| Preconditions: | none. |
| Triggers: | abt show-depends <pkg> |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User requests to view dependencies for package. 2. The dependency engine is used to generate a dependency tree (entire tree). 3. The dependency tree is displayed for user to browse (both up and down the tree). |
| Exceptions: | none. |
| Postconditions: | User has been presented a dependency tree of the given package. |

2.3.7 Show untracked files

| | |
|--------------------------------|---|
| Use Case Name: | Show untracked files |
| Description: | Finds and displays a list of files not being tracked by abt. |
| Actors: | User |
| Preconditions: | none. |
| Triggers: | abt show-untracked |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User requests to view a list of untracked files. 2. Using install logs as cross reference, list of untracked files is created. 3. Display list of untracked files. |
| Exceptions: | Missing installed packages or install log files, report error. |
| Postconditions: | User has been presented a list of untracked files on the system. |

2.3.8 Show journal

| | |
|--------------------------------|--|
| Use Case Name: | Show journal |
| Description: | Display abt journal. |
| Actors: | User |
| Preconditions: | Abt journal exists. |
| Triggers: | abt show-journal |
| Basic Course of Events: | <ol style="list-style-type: none">1. User requests to view the abt journal.2. The abt journal is displayed. |
| Exceptions: | Missing journal, report error. |
| Postconditions: | User has been presented the journal. |

2.3.9 Show file owner

| | |
|--------------------------------|--|
| Use Case Name: | Show file owner |
| Description: | Display the owning package for a given file. |
| Actors: | User |
| Preconditions: | Package owning file is installed correctly. |
| Triggers: | abt show-owner <file> |
| Basic Course of Events: | <ol style="list-style-type: none">1. User requests to view the owning package for a given file.2. The file may given as relative path or complete path.3. The install logs are searched to determine which package is owner.4. Owning package is displayed to user. |
| Exceptions: | File not found to be owned by a tracked package, show warning. |
| Postconditions: | User has been presented the name of the owning package for given file. |

2.3.10 Search package descriptions

| | |
|--------------------------------|--|
| Use Case Name: | Search package descriptions |
| Description: | Search all package descriptions for the given string, return package names that match. |
| Actors: | User |
| Preconditions: | Search string is normal string or a regexp. |
| Triggers: | abt search <string or regexp> |
| Basic Course of Events: | <ol style="list-style-type: none">1. User submits a search string.2. All package descriptions are searched for match to given string.3. Packages matching are displayed to user. |
| Exceptions: | No matching string found, return warning. |
| Postconditions: | User has been presented with a list of packages with string matches from their descriptions. |

2.3.11 Show install queue

| | |
|--------------------------------|--|
| Use Case Name: | Show install queue |
| Description: | Display the install queue contents. |
| Actors: | User |
| Preconditions: | none. |
| Triggers: | abt show-iqueue |
| Basic Course of Events: | <ol style="list-style-type: none">1. User requests to view the contents of the install queue.2. The contents of the install queue is displayed. |
| Exceptions: | Missing install queue, create install queue and report empty queue. |
| Postconditions: | User has been presented with the contents of the install queue. |

2.3.12 Show available patches

| | |
|--------------------------------|---|
| Use Case Name: | Show available patches |
| Description: | Display all available patches. |
| Actors: | User |
| Preconditions: | Network available. |
| Triggers: | abt show-patches |
| Basic Course of Events: | <ol style="list-style-type: none">1. User requests to view all available patches.2. The list of available patches is retrieved from network.3. List of available patches displayed. |
| Exceptions: | Retrieval of patch listing fails, report error. |
| Postconditions: | User has been presented a complete list of available patches. |

2.4 Generation

This section details items that need to be generated from an installed machine:

- list of packages needing updates
- HTML listing of package listing on box

2.4.1 List package updates

| | |
|--------------------------------|---|
| Use Case Name: | List package updates |
| Description: | Generate a list of updates available for installed packages. |
| Actors: | User |
| Preconditions: | Package install list and list of available updates from network are available. |
| Triggers: | abt show-updates |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User submits an updates request. 2. Package install list is processed to check each package for updates. 3. Available updates retrieved from over network. 4. User is notified by showing available updates for all installed packages. |
| Exceptions: | Warning when available update is older than installed package version. |
| Postconditions: | Package updates list has been generated. |

2.4.2 HTML package listing

| | |
|--------------------------------|--|
| Use Case Name: | HTML package listing |
| Description: | Generate HTML formatted listing of installed packages. |
| Actors: | User |
| Preconditions: | Package install list is available. |
| Triggers: | abt html |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User submits a html request. 2. Package install list is processed. 3. HTML page is generated showing installed packages list. 4. User is notified of HTML page location. |
| Exceptions: | none. |
| Postconditions: | HTML page showing package list has been generated. |

2.5 Downloads

This section details the items that involve downloading diverse components for *AbTLinux* machines:

- pull package sources
- pull package tree
- pull news feed

2.5.1 Pull package sources

| | |
|--------------------------------|--|
| Use Case Name: | Pull package sources |
| Description: | Downloading the source tarball for a given package. |
| Actors: | User |
| Preconditions: | Package description and network are available. |
| Triggers: | abt download <pkg> |
| Basic Course of Events: | <ol style="list-style-type: none">1. User requests for package source(s) to be downloaded.2. The source location is obtained from the package description.3. Support for http(s), (s)ftp, cvs and subversion.4. Source is downloaded and placed in download location. |
| Exceptions: | Source location is unreachable or gives error, report error. |
| Postconditions: | Package source(s) have been downloaded. |

2.5.2 Pull package tree

| | |
|--------------------------------|--|
| Use Case Name: | Pull package tree |
| Description: | Downloading a package tree, optionally by tree name. |
| Actors: | User |
| Preconditions: | Network is available. |
| Triggers: | abt update [name] |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User requests for package tree to be downloaded. 2. Optional name given, then look up the location in registered list (internal). 3. Support for subversion repositories. 4. Package tree is downloaded and installed. |
| Exceptions: | Source location is unreachable or gives error, report error. |
| Postconditions: | Package tree has been downloaded and installed. |

2.5.3 Pull news feed

| | |
|--------------------------------|---|
| Use Case Name: | Pull news feed |
| Description: | Downloading and view available news feed. |
| Actors: | User |
| Preconditions: | Network is available. |
| Triggers: | abt news |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User requests abt news feed download. 2. Retrieve abt news feed file. 3. Save and display news feed. |
| Exceptions: | News feed location is unreachable or gives error, warning and attempt to display old news feed file. |
| Postconditions: | News feed has been downloaded and displayed. |

2.6 Logging

This section details the requirements for keeping track of work progress with some form of logging. These items are the ones that require tracking:

- log package installation, not tracking:
 - /home
 - /tmp
 - /var/tmp
- log package files integrity information (tool to use: md5)
- log package builds
- log general progression (journal)
- cached builds include all scripts needed to build so it can always be duplicated (not lost on package maintenance in the future), track the following for each package:
 - Major version number
 - Build time (time installed package was built)
 - Configuration time (time configuration last updated)
 - Dependencies

2.6.1 Log package install

| | |
|--------------------------------|---|
| Use Case Name: | Log package install |
| Description: | What will be logged from a package install. |
| Actors: | System |
| Preconditions: | none. |
| Triggers: | The install phase of a package install. |
| Basic Course of Events: | <ol style="list-style-type: none">1. A package will reach the <i>Preinstall</i> section of package install.2. <i>Install</i> section of package is processed.3. A list of installed files is logged.4. File in following directories are not tracked:<ol style="list-style-type: none">(a) home directories.(b) tmp directories.(c) var/tmp directories. |
| Exceptions: | Any failure to create log files will be reported as error. |
| Postconditions: | Package files installed have been tracked in log file. |

2.6.2 Log package files integrity

| | |
|--------------------------------|--|
| Use Case Name: | Log package files integrity |
| Description: | A log will be created with each file a package installs being integrity checked. |
| Actors: | System |
| Preconditions: | Integrity software is available on system. |
| Triggers: | The end of install phase of a package install. |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. After files installed, the installed files log is parsed to create a checksum for each file. 2. A file can be marked as a configuration file and not tracked. 3. A file can be marked as shared and this will be noted in log. 4. A log is created containing the resulting integrity information. |
| Exceptions: | Any failure to create log files will be reported as error. |
| Postconditions: | Package files integrity information has been logged in a file. |

2.6.3 Log package build

| | |
|--------------------------------|--|
| Use Case Name: | Log package build |
| Description: | What will be logged from a package build. |
| Actors: | System |
| Preconditions: | none. |
| Triggers: | The build phase of a package install. |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. <i>Build</i> section of package is processed. 2. The running of the package build is logged to a file. |
| Exceptions: | Any failure to create log files will be reported as error. |
| Postconditions: | Package build has been logged in a file. |

2.6.4 Log journal

| | |
|--------------------------------|---|
| Use Case Name: | Log journal |
| Description: | Provide a journal of general abt activity. |
| Actors: | System |
| Preconditions: | none. |
| Triggers: | Any action abt does that is needing to be logged. |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. Any item needing to be logged will be appended to the journal with timestamp. 2. Auto journal rotation will be done at user defined number of lines or file size. |
| Exceptions: | If activity journal does not exist, it will be created. |
| Postconditions: | Abt is able to log activity to the journal. |

2.6.5 Log package cache

| | |
|--------------------------------|---|
| Use Case Name: | Log package cache |
| Description: | A complete cache of a built package, including everything needed to duplicate the build at a later date. |
| Actors: | System |
| Preconditions: | none. |
| Triggers: | The end of a package install. |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. At end of a complete package install a cache will be made, including: 2. Copy of build configuration (preserve configuration time). 3. Copy of build log (preserve build time). 4. Copy of install log. 5. Copy of package description (includes major version number). 6. Copy of source. 7. Copy of dependency tree. |
| Exceptions: | Any failure to create cache will be reported as error. |
| Postconditions: | Package build has been cached. |

2.7 Fixing

This section details requirements related to checking the health of *AbTLinux* machines and repairing any problems found:

- remove unused package sources
- remove unused package logs
- verify installed package files
- verify installed package symlinks
- verify installed package dependencies (libraries, versions)
- verify system integrity
- fix package(s)

2.7.1 Purge old package sources

| | |
|--------------------------------|---|
| Use Case Name: | Purge old package sources |
| Description: | Source tarballs will be removed for packages that are no longer installed. This will remove source tarballs for any versions of installed packages other than those currently installed. |
| Actors: | User |
| Preconditions: | Installed package list is available. |
| Triggers: | abt purge-src |
| Basic Course of Events: | <ol style="list-style-type: none">1. The user requests to remove unused package sources from system.2. The installed package list is used to determine which package (versions) to keep.3. All source tarballs from packages not currently installed are removed. |
| Exceptions: | none. |
| Postconditions: | All old source tarballs have been removed from the system. |

2.7.2 Purge old logs

| | |
|--------------------------------|---|
| Use Case Name: | Purge old logs |
| Description: | This command will query the user about removal of all old package logs (configuration, build, install, integrity) and cache logs for packages that are no longer installed. |
| Actors: | User |
| Preconditions: | Installed package list is available. |
| Triggers: | abt purge-logs |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. The user requests to remove old logs from the system. 2. The user is queried whether cache logs also need to be removed. 3. The installed package list is used to determine which package (versions) to keep. 4. All package logs are removed from the system for packages not currently installed. 5. Eventual cache logs are removed from the system for packages not currently installed. |
| Exceptions: | none. |
| Postconditions: | All old package log and eventual cache logs have been removed from the system. |

2.7.3 Verify installed package files

| | |
|--------------------------------|--|
| Use Case Name: | Verify installed package files |
| Description: | Verify that the given packages files are available on the system. |
| Actors: | User |
| Preconditions: | Package to be verified has a valid install log. |
| Triggers: | abt verify-files <pkg> |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User submits a verify files request. 2. Installed files for given package are checked if they exist by comparison to packages install log. 3. After package checked, overview of eventual missing files reported to user. |
| Exceptions: | none. |
| Postconditions: | The installed files for given package have been verified, eventual missing files have been reported. |

2.7.4 Verify installed package symlinks

| | |
|--------------------------------|---|
| Use Case Name: | Verify installed package symlinks |
| Description: | Verify that the given packages symlinks are available on the system. |
| Actors: | User |
| Preconditions: | Package to be verified has a valid install log. |
| Triggers: | abt verify-symlinks <pkg> |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User submits a verify symlinks request. 2. Installed symlinks for given package are checked if they exist by comparison to packages install log. 3. After package checked, overview of eventual missing symlinks reported to user. |
| Exceptions: | none. |
| Postconditions: | The installed symlinks for given package have been verified, eventual missing symlinks have been reported. |

2.7.5 Verify installed package dependencies

| | |
|--------------------------------|--|
| Use Case Name: | Verify installed package deps |
| Description: | Verify that the given packages dependencies are not broken (libraries). |
| Actors: | User |
| Preconditions: | Package to be verified has a valid description. |
| Triggers: | abt verify-deps <pkg> |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User submits a verify dependencies request. 2. Dependency engine used to determine given packages dependency tree. 3. Installed files for each dependency are checked for existence. 4. Installed symlinks for each dependency are checked for existence. 5. After package checked, overview of eventual broken libraries reported to user. |
| Exceptions: | none. |
| Postconditions: | The installed libraries for given package have been verified, eventual discrepancies have been reported. |

2.7.6 Verify installed package integrity

| | |
|--------------------------------|---|
| Use Case Name: | Verify installed package integrity |
| Description: | Verify given packages files integrity. |
| Actors: | User |
| Preconditions: | Package to be verified has a valid install log and md5 is available. |
| Triggers: | abt verify-integrity <pkg> |
| Basic Course of Events: | <ol style="list-style-type: none">1. User submits a verify integrity request.2. Integrity of installed files for given package are checked by comparison to packages install log.3. After package checked, overview of eventual tainted files reported to user. |
| Exceptions: | none. |
| Postconditions: | The integrity of installed files for given package have been checked, eventual tainted files have been reported. |

2.7.7 Fix package

| | |
|--------------------------------|---|
| Use Case Name: | Fix package |
| Description: | Check the package for missing/broken libraries, symlinks and file permissions. |
| Actors: | User |
| Preconditions: | Package to be fixed is installed. |
| Triggers: | abt fix [pkg] |
| Basic Course of Events: | <ol style="list-style-type: none"> 1. User submits a fix request, either on a package or on entire installed packages list if no package is given. 2. Package(s) are checked by comparing: <ol style="list-style-type: none"> (a) Installed files are checked if they exist. (b) Installed files are checked for integrity. (c) Installed libraries are checked for dependency breakage. (d) Configuration files are checked only for existence. 3. Any problems found result in User being asked if rebuild wanted. 4. Default if User does not respond is to rebuild package. 5. Check for possible dependency breakage. 6. After package(s) checked, overview of good, bad and fixed package(s) reported to User. |
| Exceptions: | Any problems results in package(s) being left in the install or uninstall queues. |
| Postconditions: | <ol style="list-style-type: none"> 1. User has report of good, bad and fixed package(s). |

2.8 Patching

This section details the requirements related to providing patching for updates and fixes on *AbTLinux* machines:

- provide for updating with a patch per package
- provide package tree patches (i.e. for entire stable tree)

2.8.1 Patch package update

| | |
|--------------------------------|---|
| Use Case Name: | Patch package update |
| Description: | Patches will be provided as preferred method of updating a package, fall-back is to use the complete updated package description. |
| Actors: | User |
| Preconditions: | Patch is available over the network and package is installed. |
| Triggers: | Any command leading to update or fix from AbTLinux network. |
| Basic Course of Events: | <ol style="list-style-type: none">1. User request leading to an update or fix being needed over the network.2. Attempt is made to retrieve needed patch over network.3. Fall-back is to retrieve needed package (entire package description) over network.4. Package is updated with patch or new package description and left in install queue. |
| Exceptions: | Patch fails to be applied, fall-back to entire package description update. |
| Postconditions: | Package has been updated with patch if available, otherwise with complete package listing. |

2.8.2 Patch package tree update

| | |
|--------------------------------|---|
| Use Case Name: | Patch package tree update |
| Description: | Patches will be provided as preferred method of updating a package tree, fall-back is to use the complete updated package tree. |
| Actors: | User |
| Preconditions: | Patch is available over the network. |
| Triggers: | Any command leading to update of the entire package tree from AbTLinux network. |
| Basic Course of Events: | <ol style="list-style-type: none">1. User request leading to an update of the entire package tree over the network.2. Attempt is made to retrieve the tree patch over network.3. Fall-back is to retrieve entire tree over network.4. Package tree is updated with patch or entire new tree. |
| Exceptions: | Patch fails to be applied, fall back to entire new tree. |
| Postconditions: | Package tree has been updated with patch if available, otherwise with complete new tree. |

2.9 Maintaining

This section details the requirements related to maintenance tasks on *AbTLinux* machines:

- provide for central build box (clients pull package builds from central box)
- provide for specification of package sources download location

2.9.1 Central build

| | |
|--------------------------------|---|
| Use Case Name: | Central build |
| Description: | Allows a single machine to function as a build center, providing cached software package builds for other machines on a network. |
| Actors: | User |
| Preconditions: | Network is available. |
| Triggers: | User setup is pointing to this central server as provider of cached software packages and requests a package install or update. |
| Basic Course of Events: | <ol style="list-style-type: none">1. User request leading to an (re)-install, update or fix of package being needed.2. User setup to direct all request to remote machine for cached packages.3. Fall-back is to search for cached packages on local machine.4. Cached package is retrieved and installed on local machine.5. A fix package check is run.6. User notified that package installed successfully. |
| Exceptions: | Unable to obtain cached package from central server, fall-back to local machine. |
| Postconditions: | Cached package has been installed and checked successfully. |

2.9.2 Source location package tree

| | |
|--------------------------------|---|
| Use Case Name: | Source location package tree |
| Description: | User can specify package tree repository, default being the AbTLinux provided repository. |
| Actors: | User |
| Preconditions: | Given repository is available and reachable. |
| Triggers: | User requests to set a package tree repository location. |
| Basic Course of Events: | <ol style="list-style-type: none">1. User provides a given URI as default package tree repository.2. Fall-back is to use the AbTLinux provided repository.3. User requests package tree update.4. Package tree is updated from given URI.5. User notified that package tree updated successfully. |
| Exceptions: | Unable to obtain package tree from URI, fall-back to AbTLinux repository. |
| Postconditions: | Package tree has been updated successfully. |

2.10 Dependencies

This section will be covered in an apart requirements document, focusing on the entire dependency engine problem. This will be a student project for the course Requirements Engineering at the Radboud University Nijmegen.

3 Scenarios

The use cases discussed in the previous section will be worked out into scenarios filled with example data or package information.

3.1 Packages

Scenarios related to the packages themselves will be found here.

| Use Case Name: | Install package |
|-----------------|---|
| Use Case Steps: | <ul style="list-style-type: none">• User command 'abt install fortune'.• fortune added to install queue.• Dependencies for this package are checked.• Missing dependencies are added to install queue (sorted before this package).• <i>Details</i> section processed:<ol style="list-style-type: none">1. NAME = fortune2. VERSION = mod-97083. SRCFILE = fortune-mod-9708.tar.gz4. SRCDIR = /usr/src/fortune-mod-97085. SRCURL = http://www.fortune.org/pub/fortune-mod-9708.tar.gz6. INTEGRITY = c016e3549942cbb7. URL = http://www.fortune.org8. LICENSE = BSD9. DESCRIPTION = "Random quotations from a large database."• <i>Pre</i> section processed:<ol style="list-style-type: none">1. Download package sources from SRCURL.2. Unpack package sources in SRCDIR.• <i>Configure</i> section of package is processed.<ol style="list-style-type: none">1. Default used, sets install location to /usr/local.2. Run configuration. |

| | |
|---------------------------------|---|
| <p>Use Case Steps:</p> | <ul style="list-style-type: none"> • Save <code>/var/state/abt/install/fortune/fortune_mod-9708.config</code>. • <i>Build</i> section processed: <ol style="list-style-type: none"> 1. Default used, run make. • Save <code>/var/state/abt/install/fortune/fortune_mod-9708.build</code>. • <i>Preinstall</i> section processed: <ol style="list-style-type: none"> 1. Default used, nothing done. item <i>Install</i> section processed: <ol style="list-style-type: none"> 1. Default used, run make install. • Save <code>/var/state/abt/install/fortune_mod-9708.install</code>. • Save <code>installed files integrity check /var/state/abt/install/fortune_mod-9708.integrity</code>. • <i>Post</i> section processed: <ol style="list-style-type: none"> 1. Check which shells are installed. 2. Add fortune message to these shell configurations. • Package sources (build directories) are cleaned up (removed). • Package is removed from install queue. • User is notified that package was successfully installed. |
| <p>Alternative Path:</p> | <ol style="list-style-type: none"> 1. Installing package that has been previously built (cached). |

| | |
|------------------------|---|
| Use Case Name: | Install package extended |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt install fortune'. • fortune added to install queue. • Dependencies for this package are checked. • Missing dependencies are added to install queue (sorted before this package). • <i>Details</i> section processed: <ol style="list-style-type: none"> 1. NAME = fortune 2. VERSION = mod-9708 3. SRCFILE = fortune-mod-9708.tar.gz 4. SRCDIR = /usr/src/fortune-mod-9708 5. SRCURL = http://www.fortune.org/pub/fortune-mod-9708.tar.gz 6. INTEGRITY = c016e3549942cbb 7. URL = http://www.fortune.org 8. LICENSE = BSD 9. DESCRIPTION = "Random quotations from a large database." • <i>Pre</i> section processed: <ol style="list-style-type: none"> 1. Download package sources from SRCURL. 2. Unpack package sources in SRCDIR. 3. Patches applied to sources. 4. User accounts created as needed. 5. Query user for any optional setting for this package. • <i>Configure</i> section of package is processed. <ol style="list-style-type: none"> 1. Set install location to /usr/local. 2. Set any default system build options (arch, flags, etc). 3. Set any options the user selected in previous section. 4. Run configuration. • Save /var/state/abt/install/fortune/fortune_mod-9708.config. |

| | |
|---------------------------------|--|
| <p>Use Case Steps:</p> | <ul style="list-style-type: none"> • <i>Build</i> section processed: <ol style="list-style-type: none"> 1. Default used, run make. 2. Run any offered (by abt API) build routines (ruby, python, perl, etc). • Save <code>/var/state/abt/install/fortune/fortune_mod-9708.build</code>. • <i>Preinstall</i> section processed: <ol style="list-style-type: none"> 1. Default used, nothing done. 2. Special steps needed to modify generated files before install done here. <p>item <i>Install</i> section processed:</p> <ol style="list-style-type: none"> 1. Default used, run make install. 2. Possible special install steps done here. <ul style="list-style-type: none"> • Save <code>/var/state/abt/install/fortune_mod-9708.install</code>. • Save <code>installed files integrity check /var/state/abt/install/fortune_mod-9708.integrity</code>. • <i>Post</i> section processed: <ol style="list-style-type: none"> 1. Check which shells are installed. 2. Add fortune message to these shell configurations. 3. Restart any services as needed. • Package sources (build directories) are cleaned up (removed). • Package is removed from install queue. • User is notified that package was successfully installed. |
| <p>Alternative Path:</p> | <ol style="list-style-type: none"> 1. Installing package that has been previously built (cached). |

| | |
|------------------------|---|
| Use Case Name: | Reinstall package |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt reinstall fortune'. • User asked if reconfigure or to use cached version of fortune. • Rebuild requested, fortune added to install queue. • Dependencies for this package are checked. • Missing dependencies are added to install queue (sorted before this package). • Packages needing rebuild after this package rebuilt added to intstall queue (sorted after this package). • Reconfigure requested: <ul style="list-style-type: none"> – Retrieve and use previous configuration as default. • <i>Details</i> section processed: <ol style="list-style-type: none"> 1. NAME = fortune 2. VERSION = mod-9708 3. SRCFILE = fortune-mod-9708.tar.gz 4. SRCDIR = /usr/src/fortune-mod-9708 5. SRCURL = http://www.fortune.org/pub/fortune-mod-9708.tar.gz 6. INTEGRITY = c016e3549942cbb 7. URL = http://www.fortune.org 8. LICENSE = BSD 9. DESCRIPTION = "Random quotations from a large database." • <i>Pre</i> section processed: <ol style="list-style-type: none"> 1. Download package sources from SRCURL. 2. Unpack package sources in SRCDIR. 3. Reconfigure requested, query user to allow for configuration changes. • <i>Configure</i> section of package is processed. <ol style="list-style-type: none"> 1. Default used, sets install location to /usr/local. 2. Run configuration. |

| | |
|---------------------------------|--|
| <p>Use Case Steps:</p> | <ul style="list-style-type: none"> • Save /var/state/abt/install/fortune/fortune_mod-9708.config. • <i>Build</i> section processed: <ol style="list-style-type: none"> 1. Default used, run make. • Save /var/state/abt/install/fortune/fortune_mod-9708.build. • <i>Preinstall</i> section processed: <ol style="list-style-type: none"> 1. Default used, nothing done. item <i>Install</i> section processed: <ol style="list-style-type: none"> 1. Default used, run make install. • Save /var/state/abt/install/fortune_mod-9708.install. • Save installed files integrity check /var/state/abt/install/fortune_mod-9708.integrity. • <i>Post</i> section processed: <ol style="list-style-type: none"> 1. Check which shells are installed. 2. Add fortune message to these shell configurations. • Package sources (build directories) are cleaned up (removed). • Package is removed from install queue. • Dependencies on this package are checked. • User is notified that package was successfully installed. |
| <p>Alternative Path:</p> | <ol style="list-style-type: none"> 1. Installing package that has been previously built (cached). |

| | |
|------------------------|---|
| Use Case Name: | Reinstall package extended |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt reinstall fortune'. • User asked if reconfigure or to use cached version of fortune. • Rebuild requested, fortune added to install queue. • Dependencies for this package are checked. • Missing dependencies are added to install queue (sorted before this package). • Packages needing rebuild after this package rebuilt added to intstall queue (sorted after this package). • Reconfigure requested: <ul style="list-style-type: none"> – Retrieve and use previous configuration as default. • <i>Details</i> section processed: <ol style="list-style-type: none"> 1. NAME = fortune 2. VERSION = mod-9708 3. SRCFILE = fortune-mod-9708.tar.gz 4. SRCDIR = /usr/src/fortune-mod-9708 5. SRCURL = http://www.fortune.org/pub/fortune-mod-9708.tar.gz 6. INTEGRITY = c016e3549942cbb 7. URL = http://www.fortune.org 8. LICENSE = BSD 9. DESCRIPTION = "Random quotations from a large database." • <i>Pre</i> section processed: <ol style="list-style-type: none"> 1. Download package sources from SRCURL. 2. Unpack package sources in SRCDIR. 3. Patches applied to sources. 4. User accounts created as needed. 5. Query user for any optional setting for this package. 6. Reconfigure requested, query user to allow for configuration changes. |

| | |
|-------------------------------|---|
| <p>Use Case Steps:</p> | <ul style="list-style-type: none"> • <i>Configure</i> section of package is processed. <ol style="list-style-type: none"> 1. Set install location to /usr/local. 2. Set any default system build options (arch, flags, etc). 3. Set any options the user selected in previous section. 4. Run configuration. • Save <code>/var/state/abt/install/fortune/fortune_mod-9708.config</code>. • <i>Build</i> section processed: <ol style="list-style-type: none"> 1. Default used, run make. 2. Run any offered (by abt API) build routines (ruby, python, perl, etc). • Save <code>/var/state/abt/install/fortune/fortune_mod-9708.build</code>. • <i>Preinstall</i> section processed: <ol style="list-style-type: none"> 1. Default used, nothing done. 2. Special steps needed to modify generated files before install done here. item <i>Install</i> section processed: <ol style="list-style-type: none"> 1. Default used, run make install. 2. Possible special install steps done here. • Save <code>/var/state/abt/install/fortune_mod-9708.install</code>. • Save installed files integrity check <code>/var/state/abt/install/fortune_mod-9708.integrity</code>. • <i>Post</i> section processed: <ol style="list-style-type: none"> 1. Check which shells are installed. 2. Add fortune message to these shell configurations. 3. Restart any services as needed. |
|-------------------------------|---|

| | |
|--------------------------|--|
| Use Case Steps: | <ul style="list-style-type: none">• Package sources (build directories) are cleaned up (removed).• Package is removed from install queue.• Dependencies on this package are checked.• User is notified that package was successfully installed. |
| Alternative Path: | <ol style="list-style-type: none">1. Installing package that has been previously built (cached). |

| | |
|------------------------|--|
| Use Case Name: | Remove package |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt remove fortune'. • fortune added to remove queue. • <i>Details</i> section processed: <ol style="list-style-type: none"> 1. NAME = fortune 2. VERSION = mod-9708 3. SRCFILE = fortune-mod-9708.tar.gz 4. SRCDIR = /usr/src/fortune-mod-9708 5. SRCURL = http://www.fortune.org/pub/fortune-mod-9708.tar.gz 6. INTEGRITY = c016e3549942cbb 7. URL = http://www.fortune.org 8. LICENSE = BSD 9. DESCRIPTION = "Random quotations from a large database." • Check to ensure package installed. • Dependencies for this package are checked. • Eventual broken dependencies are added to install queue to be rebuilt. • Retrieve fortune install info: /var/state/abt/install/fortune-mod-9708.*. <ol style="list-style-type: none"> 1. Package configure file: /var/state/abt/install/fortune-mod-9708.config. 2. Package build file: /var/state/abt/install/fortune-mod-9708.build. 3. Package install file: /var/state/abt/install/fortune-mod-9708.install. 4. Package integrity file: /var/state/abt/install/fortune-mod-9708.integrity. 5. Package sources: /var/spool/abt/fortune-mod-9708.tar.gz • <i>Preremove</i> section processed: <ol style="list-style-type: none"> 1. Process any given special instructions found here. |

| | |
|---------------------------------|--|
| <p>Use Case Steps:</p> | <ul style="list-style-type: none"> • Files cached in <code>/var/state/abt/cached/fortune/*</code>. • Process any configuration files: <ol style="list-style-type: none"> 1. Cache copies of existing configuration files: <code>fortune_mod-9708.user-configs</code>. 2. Base removal/keeping of existing configuration files on user provided option (globally set). • Create compressed tarball of all relevant logs. • Remove fortune installed files. • User notified that fortune-mod-9708 has been successfully removed. |
| <p>Alternative Path:</p> | <p>None.</p> |

| | |
|---------------------------------|---|
| <p>Use Case Name:</p> | <p>Downgrade package</p> |
| <p>Use Case Steps:</p> | <ul style="list-style-type: none"> • User command 'abt downgrade fortune mod-9707'. • fortune added to install queue. • Check to ensure fortune package installed and version higher, mod-9708. • Dependencies for package are checked. • Eventual broken dependencies are added to install queue to be rebuilt. • Run <i>remove package scenario</i> for fortune mod-9708. • Retrieve cached data for fortune mod-9707: <ol style="list-style-type: none"> 1. <code>/var/state/abt/cached/fortune/*</code>. • Unpack and reinstall the package following <i>install package scenario</i>. • User notified that fortune has been successfully downgraded. |
| <p>Alternative Path:</p> | <p>None.</p> |

| | |
|--------------------------|---|
| Use Case Name: | Freeze package |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt freeze fortune'. • Check to ensure fortune package installed. • Add fortune to the frozen packages list: <ol style="list-style-type: none"> 1. Save <code>/var/state/abt/frozen/fortune.frozen</code>. 2. This file will include a date and any other relevant information. • User notified that fortune has been successfully frozen. |
| Alternative Path: | None. |

3.2 Queries

All query related scenarios will be found here.

| | |
|--------------------------|--|
| Use Case Name: | Show package details |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt show-details fortune'. • <i>Details</i> section processed: <ol style="list-style-type: none"> 1. NAME = fortune 2. VERSION = mod-9708 3. SRCFILE = fortune-mod-9708.tar.gz 4. SRCDIR = /usr/src/fortune-mod-9708 5. SRCURL = http://www.fortune.org/pub/fortune-mod-9708.tar.gz 6. INTEGRITY = c016e3549942cbb 7. URL = http://www.fortune.org 8. LICENSE = BSD 9. DESCRIPTION = "Random quotations from a large database." • This data displayed for the user. |
| Alternative Path: | 1. Requested package is unavailabel, user receives warning. |

| | |
|--------------------------|--|
| Use Case Name: | Show installed packages |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt show-installed'. • Installed packages information is acquired from install log contents, <code>/var/log/abt/installed.log</code>. • For each package that is installed the following is displayed: <ol style="list-style-type: none"> 1. package name 2. package version 3. package install date 4. package version available (obtain from current package description). |
| Alternative Path: | 1. Unable to generate installed packages list, warn user. |

| | |
|--------------------------|---|
| Use Case Name: | Show package install |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt show-files fortune'. • Installed files information for is acquired from <code>/var/state/abt/install/fortune-mod-9708.install</code>. • The install log is displayed for the user. |
| Alternative Path: | 1. Fortune install log is not available, warn user. |

| | |
|--------------------------|---|
| Use Case Name: | Show package build |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt show-build fortune'. • Build log is acquired from <code>/var/state/abt/install/fortune-mod-9708.build</code>. • The build log is displayed for the user. |
| Alternative Path: | 1. Fortune build log is not available, warn user. |

| | |
|--------------------------|---|
| Use Case Name: | Show frozen packages |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt show-frozen'. • List of frozen packages is acquired from <code>/var/log/abt/frozen.log</code>. • The frozen packages are displayed for the user: <ol style="list-style-type: none"> 1. package name 2. package version 3. date frozen |
| Alternative Path: | 1. Frozen file is unavailable, warn user. |

| | |
|--------------------------|--|
| Use Case Name: | Show package dependencies |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt show-depends fortune'. • The depEngine is queried for a list of dependencies from fortune: <ol style="list-style-type: none"> 1. all currently installed packages that DependsOn fortune. 2. all currently installed packages that ReliesOn fortune. 3. all currently installed packages that optionally DependsOn fortune. 4. all currently installed packages that optionally ReliesOn fortune. 5. same as previous items, but that fortune (optionally) DependsOn/ReliesOn. • The list generated by the depEngine is displayed for the user: <ol style="list-style-type: none"> 1. name of package 2. version of package |
| Alternative Path: | <ol style="list-style-type: none"> 1. DepEngine is unavailable, warn user. 2. Returned list is empty of dependencies, warn user. 3. Fortune is not installed, warn user. |

| | |
|--------------------------|---|
| Use Case Name: | Show untracked files |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt show-untracked'. • Obtain the tracking information from the installed files, <code>/var/state/abt/install/*.install</code>. • Determine which files are not tracked by abt. • Return a listing of files and directories not tracked by abt. |
| Alternative Path: | 1. Tracking file is unavailable, warn user. |

| | |
|--------------------------|---|
| Use Case Name: | Show journal |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt show-journal'. • Return the contents of the abt journal log, <code>/var/log/abt/abt.log</code>. |
| Alternative Path: | <ol style="list-style-type: none"> 1. No abt journal log available, warn user. 2. Unable to access abt journal log, warn user. |

| | |
|--------------------------|---|
| Use Case Name: | Show file owner |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt show-owner <file>'. • Install logs at <code>/var/state/abt/install/*.install</code> are checked for the file. • Package name as file owner reported to user. |
| Alternative Path: | <ol style="list-style-type: none"> 1. File not found in install logs, report to user. 2. File submitted was not full path can result in multiple package results. |

| | |
|--------------------------|--|
| Use Case Name: | Search package descriptions |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt search <string/regexp>'. • Search all package descriptions for the given string/regexp. • Report list of package names with descriptions that match the search string/regexp. |
| Alternative Path: | <ol style="list-style-type: none"> 1. No matches to string/regexp found, report to user. 2. No package descriptions available, warn to user. |

| | |
|--------------------------|---|
| Use Case Name: | Show install queue |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt show-iqueue'. • Display the contents of the install queue, <code>/var/log/abt/install.queue</code>. |
| Alternative Path: | <ol style="list-style-type: none"> 1. Install queue file is non-existent or empty, report to user. |

| | |
|--------------------------|---|
| Use Case Name: | Show available patches |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt show-patches'. • Generate a patch from the available package repository with 'svn diff -r REPO-NAME' • Provide user with a view of a patch difference between current package listing and available package repository. |
| Alternative Path: | <ol style="list-style-type: none"> 1. Unable to generate repository difference, warn user. |

3.3 Generation

These scenarios relate to the generation of package information.

| | |
|--------------------------|--|
| Use Case Name: | List package updates |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt show-updates'. • Compare installed packages listing to current package descriptions. • Generate listing of packages that have a newer version in the current package descriptions. • Present user with listing of available updates; package name, current version, update version. |
| Alternative Path: | <ol style="list-style-type: none"> 1. Installed packages listing is unavailable, warn user. 2. Package description for some package is unavailable, include line in results; package name, current version, unknown. |
| Use Case Name: | HTML package listing |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt html'. • Generate HTML page from installed packages listing; package name with hyperlink to website, version installed. |
| Alternative Path: | <ol style="list-style-type: none"> 1. Installed package listing unavailable, warn user. |

3.4 Downloads

Here you find the scenarios related to downloading packages, updates and news.

| | |
|--------------------------|--|
| Use Case Name: | Pull package sources |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt download fortune'. • Obtain from fortune package description the SRCURL, <code>http://www.fortune.org/pub/fortune-mod-9708.tar.gz</code>. • Download the fortune source file to <code>/var/spool/abt</code>. • Report to user that download successful. |
| Alternative Path: | <ol style="list-style-type: none"> 1. Fortune description is not available, warn user. 2. Fortuen source file location not reachable, warn user. 3. Support http(s), (s)ftp, cvs and subversion downloads. |
| Use Case Name: | Pull package tree |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt update <name>'. • If name is given, then update only that package tree via the source location entry. • Otherwise update all registered package trees. • Package tree(s) updated, 'svn -r REPO-NAME update'. • Report to user update was successful. |
| Alternative Path: | <ol style="list-style-type: none"> 1. Package tree name not in listing, provide user with dialog to add new entry. 2. Package tree location unreachable, warn user. |

| | |
|--------------------------|---|
| Use Case Name: | Pull new feed |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt news'. • The AbTLinux website newsfeed is retrieved (RSS). • The news is saved at location <code>/var/log/abt/news.log</code>. • News is displayed for the user. |
| Alternative Path: | <ol style="list-style-type: none"> 1. AbTLinux newsfeed is unreachable, attempt to display old newsfeed file. 2. Old newsfeed file unavailable, warn user. |

3.5 Logging

All logging scenarios will be presented here.

| | |
|--------------------------|--|
| Use Case Name: | Log package install |
| Use Case Steps: | <ul style="list-style-type: none"> • Package fortune install reaches the install section. • During install the files copied to the system. • These installed files are noted in file <code>/var/state/abt/install/fortune/fortune_mod-9708.install</code>. |
| Alternative Path: | <ol style="list-style-type: none"> 1. Installed files listed in <code>/etc/abt/tracking.info</code> will not be included in install log. 2. Files that are installed as symlinks to another file are noted in the install log. |

| | |
|--------------------------|---|
| Use Case Name: | Log package file integrity |
| Use Case Steps: | <ul style="list-style-type: none"> • Package fortune install reaches completion. • Integrity check run on each file listed in <code>/var/state/abt/install/fortune/fortune_mod-9708.install</code>. • Save file integrity checks in <code>/var/state/abt/install/fortune/fortune_mod-9708.integrity</code>. |
| Alternative Path: | <ol style="list-style-type: none"> 1. Integrity tools are unavailable, warn user. 2. Install file unavailable, warn user. |

| | |
|--------------------------|---|
| Use Case Name: | Log package build |
| Use Case Steps: | <ul style="list-style-type: none"> • Package fortune runs the build section. • The build log is saved to <code>/var/state/abt/install/fortune/fortune_mod-9708.build</code>. |
| Alternative Path: | 1. None. |

| | |
|--------------------------|--|
| Use Case Name: | Log journal |
| Use Case Steps: | <ul style="list-style-type: none"> • Any part of abt may call for a logging action. • Action message is logged to the journal <code>/var/log/abt/abt.log</code> with a timestamp. |
| Alternative Path: | 1. Journal log file is unavailable, warn user. |

| | |
|--------------------------|--|
| Use Case Name: | Log package cache |
| Use Case Steps: | <ul style="list-style-type: none"> • At completion of successful install or removal of the fortune package. • The following will be caches at <code>/var/state/abt/abtd/fortune/</code>: <ol style="list-style-type: none"> 1. copy of fortune-mod-9708.config 2. copy of fortune-mod-9708.build 3. copy of fortune-mod-9708.install 4. copy of fortune-mod-9708.integrity 5. copy of fortune configuration options (setting user specified) 6. copy of current configuration files 7. copy of fortune package description 8. copy of fortune sources • This set of data will be tarballed and compressed for storage. |
| Alternative Path: | 1. Any item missing in the above list, warn user. |

3.6 Fixing

Scenarios dealing with fixing package problems are detailed here.

| | |
|--------------------------|--|
| Use Case Name: | Purge old package sources |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt purge-src'. • Install log is accessed from <code>/var/log/abt/installed.log</code>. • Each package description is accessed for sources name that appears in the install log. • In source storage <code>/var/spool/abt/</code>, any package sources found not installed will be removed. • Note removed packages sources in journal. • Report amount of freed disk space to user. |
| Alternative Path: | <ol style="list-style-type: none"> 1. Installed packages log is unavailable, warn user. 2. Package descriptions are unavailable, warn user. 3. If unsure about a package source, default is to remove it. |

| | |
|--------------------------|--|
| Use Case Name: | Purge old logs |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt purge-logs'. • User is queried if old caches should also be removed. • Install log is accessed from <code>/var/log/abt/installed.log</code>. • Each package in <code>/var/state/abt/install/</code> is checked against the installed log. • Any package found not installed will be removed. • If user specified old caches to be removed, same check is done on <code>/var/state/abt/cached/</code> entries. • Note removed packages sources in journal. • Report amount of freed disk space to user. |
| Alternative Path: | <ol style="list-style-type: none"> 1. Installed packages log is unavailable, warn user. 2. Package descriptions are unavailable, warn user. 3. If unsure about a package log or cache, default is to leave it in place. |

| | |
|--------------------------|--|
| Use Case Name: | Verify installed package files |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt verify-files fortune'. • Install log for fortune is accessed at <code>/var/state/abt/install/fortune/fortune-mod-9807.install</code>. • Each file is checked for existence. • User supplied with overview of any missing files. |
| Alternative Path: | <ol style="list-style-type: none"> 1. Install log unavailable, warn user. 2. No files fail the check, inform user. |

| | |
|--------------------------|--|
| Use Case Name: | Verify installed package symlinks |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt verify-symlinks fortune'. • Install log for fortune is accessed at <code>/var/state/abt/install/fortune/fortune-mod-9807.install</code>. • Each file marked as a symlink is checked for existence as symlink. • User supplied with overview of any symlinked files failing check. |
| Alternative Path: | <ol style="list-style-type: none"> 1. Install log unavailable, warn user. 2. No files fail the check, inform user. |

| | |
|--------------------------|--|
| Use Case Name: | Verify installed package deps |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt verify-deps fortune'. • depEngine requested to determine dependencies dntree for fortune. • Each package in dntree list is checked with: <ol style="list-style-type: none"> 1. abt verify-files DOWNTREE-PKG 2. abt verify-symlinks DOWNTREE-PKG 3. abt verify-integrity DOWNTREE-PKG • User supplied with overview of any broken dependencies. |
| Alternative Path: | <ol style="list-style-type: none"> 1. depEngine unavailable, warn user. 2. Log actions to journal. |

| | |
|--------------------------|---|
| Use Case Name: | Verify installed package integrity |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt verify-integrity fortune'. • Install log for fortune is accessed at <code>/var/state/abt/install/fortune/fortune-mod-9807.install</code>. • Integrity log for fortune is accessed at <code>/var/state/abt/install/fortune/fortune-mod-9807.integrity</code>. • Each file is checked for integrity. • User supplied with overview of any files failing check. |
| Alternative Path: | <ol style="list-style-type: none"> 1. Install log unavailable, warn user. 2. Integrity log unavailable, warn user. 3. No files fail the integrity check, inform user. |

| | |
|--------------------------|---|
| Use Case Name: | Fix package |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt fix fortune'. <ol style="list-style-type: none"> 1. abt verify-files fortune 2. abt verify-symlinks fortune 3. abt verify-integrity fortune • depEngine requested to determine dependencies dntree for fortune. • Each package in dntree list is checked with: <ol style="list-style-type: none"> 1. abt verify-files DOWNTREE-PKG 2. abt verify-symlinks DOWNTREE-PKG 3. abt verify-integrity DOWNTREE-PKG • User supplied with overview of any broken dependencies. • User offered to rebuild broken package list. • After rebuild, report broken and fixed packages. |
| Alternative Path: | <ol style="list-style-type: none"> 1. No package name is given, process entire installed packages log. |

3.7 Patching

Scenarios dealing with patching both packages and package trees are presented here.

| | |
|--------------------------|--|
| Use Case Name: | Patch package update |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt update fortune'. • Package is updated from the repository, 'svn -r REPO-NAME PATH-TO-PACKAGE/fortune'. • Report fortune updated. |
| Alternative Path: | 1. Unable to reach package repository, warn user. |

| | |
|--------------------------|---|
| Use Case Name: | Patch package tree update |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt update'. • Package tree is updated from repository, 'svn -r REPO-NAME update'. • Report package tree updated. |
| Alternative Path: | 1. Unable to reach package repository, warn user. |

3.8 Maintaining

Several maintenance scenarios are presented here.

| | |
|--------------------------|---|
| Use Case Name: | Central build |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt build-location <HOST>'. • Default is localhost. • User can set any host that is used to build packages. • All package checks for caching and building are run via the provided HOST. • User notified that new location has been set. |
| Alternative Path: | <ol style="list-style-type: none"> 1. Given HOST is unreachable, do not update build-location setting, warn user. 2. If no HOST is given, report current setting. |

| | |
|--------------------------|--|
| Use Case Name: | Source location package tree |
| Use Case Steps: | <ul style="list-style-type: none"> • User command 'abt package-repository (add remove list) <URI>'. • The list command will display all current repository locations in order. • The add command will add new location. • The remove command will remove a location. • The URI need only be a valid svn package repository. • The AbTLinux package repository will always be the last fallback repository. • The new locations are run to update the package trees. • User notified that the package tree locations have been updated and is shown a listing. |
| Alternative Path: | <ol style="list-style-type: none"> 1. Package location is not reachable, do not add repository and warn user. |

4 Dictionary

A list can be found here that contains terms and their AbTLinux related definitions. Hopefully this will keep everyone on the same page.

- **Package** - this will contain all needed information for the abt tool to install a single piece of software.
- **abt** - the package manager tool that can be run from the command line and provides for all software management on the AbTLinux distribution.
- **depEngine** - the dependency engine, part of the tool set used by 'abt' to facilitate package management.
- **Dependency** - a package X will have a dependency on another package Y if X needs a service provided by Y. X is then dependent on Y.
- **AbTLinux** - the name of this distribution, derived from ABout Time Linux.
- **Journal** - the running log of abt actions, where 'abt' will provide information as to actions taken on the AbTLinux system.

5 Thanks

This is to thank those whose input and critical eyes have been on this document since the early days of its conception. I will list them in alphabetical order:

- Bas van Gils for his proof reading and insistent nature that keeps me busy.
- Benoit Papillault for his freely given time and support with all projects we have worked on together.
- Jose Silva, another critical eye and stable spirit in the often turbulent world of free software development.
- Tony Smith who has been my verbal Linux sparring partner for a long time.
- Laurent Wandrebeck who is a pretty sharp DB cookie and long time partner in Linux crimes.

Thanks guys!

Special mention: the Source Mage GNU/Linux team - For good or bad my experiences with you taught me much, for that I am forever greatfull. You are always welcome in my world!

References

Easinstaller (2004). *Easinstaller website*.

<http://easinstaller.sourceforge.net>. last checked 23 Sep, 2004.

micropkg (2004). *The Micro Package Manager website*.

<http://u-os.org/upm.html>. last checked 23 Sep, 2004.

SMGL (2004). *Source Mage GNU/Linux website*.

<http://www.sourcemage.org>. last checked 23 Sep, 2004.